



BC112H-N1/EP \$18,593.66 USD

SKU: e082dda2ee1d Categories: Encapsulated Isolation Transformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

Weight	1365 lbs
Phases	<u>3</u>
kVA	<u>112.5</u>
Connection	<u>3Ph-DY-5T-SD</u>
Primary Voltage	<u>480</u>
Primary Max Current	<u>135.3A</u>
Primary Markings	<u>H1-H2-3</u>
Primary Terminals	<u>300MCM-6</u>





Secondary Voltage	<u>400Y/231</u>
Secondary Markings	<u>X0-X1-X2-X3</u>
Secondary Terminals	<u>300MCM-6</u>
Primary Taps	<u>+/-2 x 2.5%</u>
Conductor Material	<u>Copper</u>
Temperatue Rise	<u>130°C</u>
Insuation Class	<u>200°C</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency	N/A
Impedance	<u>1.5 – 3.5%</u>
Sound (db)	<u>50</u>
Enclosure Type	NEMA 3R Indoor
Enclosure	E3R-3PEP-8
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered