

OFFICIAL QUOTE

2500KVA 460 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER





2500KVA 460 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER


\$33,929.30 CAD

Three Phase Autotransformer with a capacity of 2500kVA, transforming 460Y Volts to 550Y Volts

SKU: RA2500H1-J2

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 2500kVA, transforming 460Y Volts to 550Y Volts



OFFICIAL QUOTE

2500KVA 460 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	2604 lbs
Phases	<u>3</u>
kVA	2500
Connection	3PhA-NT-1
Primary Voltage	460
Primary Max Current	3137.8A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	<u>550</u>
Secondary Max Current	2624.3A
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 - 1.5%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-10
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

2500KVA 460 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------