



**RS10C**

**\$841.00 CAD**

SKU: dea51b1c8684

Categories: [Motor Starters](#)

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



#### PRODUCT SPECIFICATIONS

|                     |                             |
|---------------------|-----------------------------|
| Weight              | 40 lbs                      |
| Phases              | <a href="#">3</a>           |
| HP                  | <a href="#">10</a>          |
| Connection          | <a href="#">3PhA-ST-0-2</a> |
| Primary Voltage     | <a href="#">240</a>         |
| Primary Max Current | <a href="#">24.1A</a>       |



|                            |                                                                                                      |
|----------------------------|------------------------------------------------------------------------------------------------------|
| Primary Markings           | <a href="#">H1-H2-H3</a>                                                                             |
| Primary Terminals          | <a href="#">Large Screws</a>                                                                         |
| Secondary Voltage          | <a href="#">65/80/100%</a>                                                                           |
| Secondary Max Current      | <a href="#">88.8A</a>                                                                                |
| Secondary Markings         | <a href="#">A-B-C</a>                                                                                |
| Secondary Terminals        | <a href="#">Large Screws</a>                                                                         |
| Primary Taps               | <a href="#">N/A</a>                                                                                  |
| Conductor Material         | <a href="#">Copper</a>                                                                               |
| Temperatue Rise            | <a href="#">115°C</a>                                                                                |
| Insuation Class            | <a href="#">180°C</a>                                                                                |
| BIL (Insulation) Level     | <a href="#">10kV</a>                                                                                 |
| Efficiency                 | <a href="#">N/A</a>                                                                                  |
| Impedance                  | <a href="#">N/A</a>                                                                                  |
| Sound (db)                 | <a href="#">N/A</a>                                                                                  |
| Enclosure Type             | <a href="#">Core &amp; Coil</a>                                                                      |
| Enclosure                  | <a href="#">N/A</a>                                                                                  |
| Finish                     | <a href="#">N/A</a>                                                                                  |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |