



25KVA 415 VOLTS TO 575 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$1,733.70 CAD

Single Phase Autotransformer with a capacity of
25kVA, transforming 415 Volts to 575 Volts

SKU: MC25G2-J1

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 25kVA, transforming 415 Volts to 575 Volts



PRODUCT SPECIFICATIONS

Weight	99.8 lbs
Phases	1
kVA	25
Connection	1PhA-NT-1
Primary Voltage	415
Primary Max Current	34.8A
Primary Markings	X0-X1
Primary Terminals	Terminal Blocks
Secondary Voltage	575
Secondary Max Current	25.1A
Secondary Markings	H0-H1
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-2
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

25KVA 415 VOLTS TO 575 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------