


OFFICIAL QUOTE

15KVA 208 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER





15KVA 208 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$1,783.80 CAD


Single Phase Autotransformer with a capacity of 15kVA, transforming 208 Volts to 440 Volts

SKU: MC15B-H2

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 15kVA, transforming 208 Volts to 440 Volts



OFFICIAL QUOTE



15KVA 208 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	105.1 lbs
Phases	1
kVA	<u>15</u>
Connection	1PhA-NT-1
Primary Voltage	208
Primary Max Current	41.6A
Primary Markings	<u>X0-X1</u>
Primary Terminals	#2-14 AWG
Secondary Voltage	440
Secondary Max Current	19.7A
Secondary Markings	H0-H1
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	<u>1.5 – 3.5%</u>
Sound (db)	40 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-4
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

15KVA 208 VOLTS TO 440 VOLTS SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------