

OFFICIAL QUOTE

150KVA 208 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER





150KVA 208 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER


\$8,218.40 CAD

Three Phase Autotransformer with a capacity of 150kVA, transforming 208Y Volts to 575Y Volts

SKU: RA150B-J1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 150kVA, transforming 208Y Volts to 575Y Volts



OFFICIAL QUOTE



150KVA 208 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	639 lbs
Phases	<u>3</u>
kVA	150
Connection	3PhA-NT-1
Primary Voltage	208
Primary Max Current	416.4A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	<u>575</u>
Secondary Max Current	<u>150.6A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>2.5 - 4.5%</u>
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

150KVA 208 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------