

OFFICIAL QUOTE

150KVA 120 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER






150KVA 120 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER

\$9,013.30 CAD

Three Phase Autotransformer with a capacity of 150kVA, transforming 120Y Volts to 400Y Volts

SKU: RA150A-G1 Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 150kVA, transforming 120Y Volts to 400Y Volts



OFFICIAL QUOTE

150KVA 120 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| Weight | 710 lbs |
|----------------------------|---|
| Phases | <u>3</u> |
| kVA | <u>150</u> |
| Connection | <u>3PhA-NT-1</u> |
| Primary Voltage | 120 |
| Primary Max Current | <u>721.7A</u> |
| Primary Markings | <u>X1-X2-X3</u> |
| Primary Terminals | Pads |
| Secondary Voltage | <u>400</u> |
| Secondary Max Current | <u>216.5A</u> |
| Secondary Markings | <u>H1-H2-H3</u> |
| Secondary Terminals | 600MCM-2 |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insulation Class | <u>220°C (Class H)</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | <u>N/A</u> |
| Impedance Range | <u>2.5 - 4.5%</u> |
| Sound (db) | <u>55</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-8</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

150KVA 120 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM