

#### **OFFICIAL QUOTE**

## 112KVA 416 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER





### 112KVA 416 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER


\$6,956.40 CAD


Three Phase Autotransformer with a capacity of 112.5kVA, transforming 416Y Volts to 115Y Volts

**SKU:** RA112G-A1

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 112.5kVA, transforming 416Y Volts to 115Y Volts



### **OFFICIAL QUOTE**



# 112KVA 416 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

#### PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	527 lbs
Phases	<u>3</u>
kVA	112.5
Connection	3PhA-NT-1
Primary Voltage	416
Primary Max Current	<u>156.1A</u>
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	300MCM-6
Secondary Voltage	115
Secondary Max Current	<u>564.8A</u>
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>2.5 – 4.5%</u>
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

# 112KVA 416 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------