

OFFICIAL QUOTE

112KVA 110 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER





112KVA 110 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER


\$7,851.60 CAD


Three Phase Autotransformer with a capacity of 112.5kVA, transforming 110Y Volts to 600Y Volts

SKU: RA112A2-J

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 112.5kVA, transforming 110Y Volts to 600Y Volts



OFFICIAL QUOTE





PRODUCT SPECIFICATIONS

| Wainba | 606 lbs |
|----------------------------|--|
| Weight | 606 IDS |
| Phases | 3 |
| kVA | 112.5 |
| Connection | <u>3PhA-NT-1</u> |
| Primary Voltage | 110 |
| Primary Max Current | <u>590.5A</u> |
| Primary Markings | <u>X1-X2-X3</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 600 |
| Secondary Max Current | 108.3A |
| Secondary Markings | <u>H1-H2-H3</u> |
| Secondary Terminals | #2/0-6 AWG |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>2.5 – 4.5%</u> |
| Sound (db) | <u>55</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-8 |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

112KVA 110 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|