

OFFICIAL QUOTE

200KVA 230 VOLTS TO 416 VOLTS SINGLE PHASE AUTOTRANSFORMER





200KVA 230 VOLTS TO 416 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$9,622.50 CAD

Single Phase Autotransformer with a capacity of 200kVA, transforming 230 Volts to 416 Volts

SKU: MC200C1-G

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 200kVA, transforming 230 Volts to 416 Volts



OFFICIAL QUOTE

200KVA 230 VOLTS TO 416 VOLTS SINGLE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| Weight | 714.2 lbs |
|----------------------------|--|
| Phases | 1 |
| kVA | 200 |
| Connection | 1PhA-NT-1 |
| Primary Voltage | 230 |
| Primary Max Current | <u>502A</u> |
| Primary Markings | <u>X0-X1</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 416 |
| Secondary Max Current | 277.6A |
| Secondary Markings | <u>H0-H1</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.5 - 3.5% |
| Sound (db) | <u>55 dB</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-8S</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

200KVA 230 VOLTS TO 416 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|