



BC3J-M \$1,213.70 USD

SKU: 6d5e7af9ccf6 Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

Weight	80 lbs
Phases	<u>3</u>
kVA	<u>3</u>
Connection	<u>3Ph-DY-3T-SD</u>
Primary Voltage	<u>600</u>
Primary Max Current	<u>2.9A</u>
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	Terminal Blocks

The quote is valid 30 days from 18 April 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



BC3J-M



Secondary Voltage	208Y/120
Secondary Max Current	<u>8.3A</u>
Secondary Markings	<u>X0-X1-X2-X3</u>
Secondary Terminals	Terminal Blocks
Primary Taps	<u>+/-1 x 5%</u>
Conductor Material	Copper
Insuation Class	<u>180°C</u>
BIL (Insulation) Level	<u>10kV</u>
Impedance	<u>5.5 - 7.0%</u>
Sound (db)	<u>40</u>
Enclosure Type	NEMA 1
Enclosure	<u>E1-3</u>
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered