


MP3C9H-M

\$6,165.73 USD


SKU: 1e8eee0036bd

Categories: [Mini Power Centers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



| Ref | A | B | C | D | E | F | G | H |
|--------------|----|------|------|------|------|---|------|------|
| Dim (inches) | 18 | 12.5 | 43.5 | 15.6 | 27.9 | 8 | 14.5 | 20.1 |





PRODUCT SPECIFICATIONS

| | |
|---------------------------------------|--|
| Weight | 315 lbs |
| Phases | 3 |
| Circuit Breaker Suitability | Eaton Type BR |
| kVA | 9 |
| Connection | MPC3P-3t |
| Incoming Voltage | 480 |
| Primary Breaker | 25A |
| Interrupting Rating | 14kAIC @ 480V |
| Output Voltage | 208Y/120 |
| Secondary Breaker | 30A |
| Short Circuit Withstand | 10kAIC @ 240V |
| Primary Taps | +/- 1 x 5% |
| Conductor Material | Copper |
| Insuation Class | 200°C |
| Panel Board | Push-On |
| Load Center Bus Material | Aluminum |
| # of Circuits | 12 |
| Impedance | 1.5 – 3.0% |
| Temperatue Rise | 130°C |
| Enclosure | E3R-3PMPC-1 |
| Enclosure Type | E3R Outdoor |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E495724, ISO 9001:2015 Registered |