



25VA 600 VOLTS TO 240/480 VOLTS SINGLE PHASE CONTROL TRANSFORMER

\$94.64 CAD

Single Phase Control Transformer with a capacity of 25VA, transforming 600 Volts to 240/480 Volts

SKU: CS25J-L

Categories: [Control Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES

Control Transformers - Table of Dimensions (inches)						
VA Rating	Overall Dimensions				Mounting Slot	
	A	B	C	F	W	D
25	3	3	2.5	2.5	0.118	0.25 x 0.625
50	3	3	2.5	2.5	0.118	0.25 x 0.625
100	3	4	2.5	2.5	0.118	0.25 x 0.625
150	3.75	4.25	3.13	3.25	0.118	0.25 x 0.625
200	3.75	4.5	3.13	3.25	0.118	0.25 x 0.625
250	3.75	5	3.13	3.25	0.118	0.25 x 0.625
300	4.5	5	3.75	3.75	0.118	0.31 x 0.625
350	5.25	5	4.38	4.5	0.118	0.31 x 0.625
400	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
450	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
500	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
550	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
600	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
650	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
700	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
750	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
800	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
850	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
900	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
950	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1000	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1100	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1200	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1300	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1400	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1500	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1600	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1700	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1800	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
1900	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
2000	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
2200	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
2400	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
2600	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
2800	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
3000	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
3200	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
3400	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
3600	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
3800	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
4000	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
4200	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
4400	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
4600	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
4800	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625
5000	5.25	5.5	4.38	4.5	0.118	0.31 x 0.625



Single Phase Control Transformer with a capacity of 25VA, transforming 600 Volts to 240/480 Volts



PRODUCT SPECIFICATIONS

Weight	2.3 lbs
Phases	1
Connection	1Ph-CT-SD-SD
Primary Voltage	600
Primary Max Current	0.04A
Primary Markings	H1-H2
Primary Terminals	Terminals
Secondary Voltage	240/480
Secondary Max Current	0.1A
Secondary Markings	X1-X2-X3-X4
Secondary Terminals	Terminals
Primary Taps	N/A
Conductor Material	Copper
Temperatue Rise	80°C
Insuation Class	130°C (Class B)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	5.0 – 7.0%
Sound (db)	40
Enclosure Type	Core & Coil
Enclosure Size	See Core & Coil Chart
Finish/Colour	N/A
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered



OFFICIAL QUOTE
25VA 600 VOLTS TO 240/480 VOLTS
SINGLE PHASE CONTROL
TRANSFORMER



VA	
Country/Manufacturer	Canada/RPM