



RA112J-B

\$5,457.24 USD

SKU: c5d656ca5498

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

| | |
|--------|-----------------------|
| Weight | 500 lbs |
| Phases | 3 |
| kVA | 112.5 |



| | |
|---------------------------------------|--|
| Connection | 3PhA-NT-1 |
| Primary Voltage | 600 |
| Primary Max Current | 108.3A |
| Primary Markings | H1-H2-H3 |
| Primary Terminals | 300MCM-6 |
| Secondary Voltage | 208 |
| Secondary Max Current | 312.3A |
| Secondary Markings | X1-X2-X3 |
| Secondary Terminals | Pads |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insuation Class | 220°C |
| BIL (Insulation) Level | 10kV |
| Efficiency | N/A |
| Impedance | 2.5 – 4.5% |
| Sound (db) | 45 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-7 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |