




RS15J

\$869.00 CAD

SKU: 7edd22c13bb5

Categories: [Motor Starters](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

| | |
|---------------------|-----------------------------|
| Weight | 45 lbs |
| Phases | 3 |
| HP | 15 |
| Connection | 3PhA-ST-0-2 |
| Primary Voltage | 600 |
| Primary Max Current | 14.4A |



| | |
|----------------------------|------------------------------------------------------------------------------------------------------|
| Primary Markings | H1-H2-H3 |
| Primary Terminals | Large Screws |
| Secondary Voltage | 65/80/100% |
| Secondary Max Current | 133.2A |
| Secondary Markings | A-B-C |
| Secondary Terminals | Large Screws |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Temperatue Rise | 115°C |
| Insuation Class | 180°C |
| BIL (Insulation) Level | 10kV |
| Efficiency | N/A |
| Impedance | N/A |
| Sound (db) | N/A |
| Enclosure Type | Core & Coil |
| Enclosure | N/A |
| Finish | N/A |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |