

OFFICIAL QUOTE

500VA 240/480 VOLTS TO 12/24 VOLTS SINGLE PHASE CONTROL TRANSFORMER





500VA 240/480 VOLTS TO 12/24 VOLTS SINGLE PHASE CONTROL TRANSFORMER

\$373.10 CAD


Single Phase Control Transformer with a capacity of 500VA, transforming 240/480 Volts to 12/24 Volts

SKU: CE500L-Z

Categories: Control Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES

Control				Dimensions	s (inches)
VA	Overall Dimensions				
Rating	A	В	С	Mounting Dimensions D x E	
25	3	6	3.5	1.375	4.375
50	3	6	3.5	1.375	4.375
100	3	6	3.5	1.375	4.375
150	3.5	6.658	3.13	3.25	5
200	3.5	6.658	3.13	3.25	5
250	3.5	6.658	3.13	3.25	5
350	4.125	6.5	3.75	3.75	7.875
500	4.875	7	4.38	4.5	5.5
750	4.875	7	4.38	4.5	5.5
1000	4.875	7	4.38	4.5	5.5
1500	5.625	9	5.63	5	7.25
2000	6.875	9.25	6.25	6	8
3000	6.875	9.25	6.25	6	8
5000	8	10.5	9.5	6	9



Single Phase Control Transformer with a capacity of 500VA, transforming 240/480 Volts to 12/24 Volts



OFFICIAL QUOTE



500VA 240/480 VOLTS TO 12/24 VOLTS SINGLE PHASE CONTROL TRANSFORMER

PRODUCT SPECIFICATIONS

RODUCT SPECIFICATIONS				
Weight	14 lbs			
Phases	1			
Connection	1Ph-CT-DD-SD			
Primary Voltage	240/480			
Primary Max Current	2.08A			
Primary Markings	H1-H2-H3-H4			
Primary Terminals	Leads			
Secondary Voltage	12/24			
Secondary Max Current	41.67A			
Secondary Markings	<u>X1-X2-X3-X4</u>			
Secondary Terminals	Leads			
Primary Taps	N/A			
Conductor Material	<u>Copper</u>			
Temperatue Rise	115°C			
Insuation Class	180°C (Class F)			
BIL (Insulation) Level	<u>10kV</u>			
Efficiency (@35% Load) %	N/A			
Impedance Range	<u>5.0 – 7.0%</u>			
Sound (db)	40			
Enclosure Type	Type-1 Indoor			
Enclosure Size	See Enclosure Chart			
Finish/Colour	Semigloss - Black			
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered			



OFFICIAL QUOTE



500VA 240/480 VOLTS TO 12/24 VOLTS SINGLE PHASE CONTROL TRANSFORMER

VA	
Country/Manufacturer	Canada/RPM