


MP3A30H-M/BO/CLC

\$10,063.86 USD

SKU: efba06f32e1d

Categories: [Mini Power Centers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Ref	A	B	C	D	E	F	G	H
Dim (inches)	23.25	14.5	60	23.6	36.5	8	26.5	25.38





PRODUCT SPECIFICATIONS

Weight	710 lbs
Phases	3
kVA	30
Circuit Breaker Suitability	Eaton Type BAB
Conductor Material	Aluminum
Connection	MPC3P-5t
Incoming Voltage	480
Primary Breaker	80A
Interrupting Rating	14kAIC @ 480V
Output Voltage	208Y/120
Secondary Breaker	100A
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	+/- 2 x 2.5%
Insuation Class	200°C
Panel Board	Bolt-On
Load Center Bus Material	Copper
# of Circuits	30
Impedance	1.5 – 3.0%
Temperatue Rise	130°C
Enclosure	E3R-1PMPC-3B
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, ISO 9001:2015 Registered