



MP3A45J-M/B0/CLC \$14,886.27 USD

SKU: 30ca0c941368 Categories: <u>Mini Power Centers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





The quote is valid 30 days from 5 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



MP3A45J-M/BO/CLC



PRODUCT SPECIFICATIONS

| Weight | 960 lbs |
|-----------------------------|--|
| Phases | <u>3</u> |
| Circuit Breaker Suitability | Eaton Type BAB |
| kVA | <u>45</u> |
| Connection | MPC3P-5t |
| Incoming Voltage | <u>600</u> |
| Primary Breaker | <u>90A</u> |
| Interruping Rating | <u>14kAIC @ 600V</u> |
| Output Voltage | <u>208Y/120</u> |
| Secondary Breaker | <u>150A</u> |
| Short Circuit Withstand | 25kAIC @ 240V |
| Primary Taps | <u>+/- 2 x 2.5%</u> |
| Conductor Material | Aluminum |
| Insuation Class | <u>200°C</u> |
| Panel Board | Bolt-On |
| Load Center Bus Material | <u>Copper</u> |
| # of Circuits | <u>30</u> |
| Impedance | <u>1.5 – 3.0%</u> |
| Temperatue Rise | <u>130°C</u> |
| Enclosure | E3R-3PMPC-4B |
| Enclosure Type | E3R Outdoor |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, ISO 9001:2015 Registered |

The quote is valid 30 days from 5 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.