


MP3A45J-M/B0/CLC

\$14,886.27 USD


SKU: 30ca0c941368

Categories: [Mini Power Centers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Ref	A	B	C	D	E	F	G	H
Dim (inches)	25.5	18	65	23.5	41.5	8	29.5	27.6





PRODUCT SPECIFICATIONS

Weight	960 lbs
Phases	3
Circuit Breaker Suitability	Eaton Type BAB
kVA	45
Connection	MPC3P-5t
Incoming Voltage	600
Primary Breaker	90A
Interrupting Rating	14kAIC @ 600V
Output Voltage	208Y/120
Secondary Breaker	150A
Short Circuit Withstand	25kAIC @ 240V
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
Insulation Class	200°C
Panel Board	Bolt-On
Load Center Bus Material	Copper
# of Circuits	30
Impedance	1.5 – 3.0%
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-4B
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, ISO 9001:2015 Registered