




# MC100H-C

## \$3,565.25 USD

SKU: 9dba642c5936  
Categories: [Autotransformer](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



### PRODUCT SPECIFICATIONS

|                 |                           |
|-----------------|---------------------------|
| Weight          | 320 lbs                   |
| Phases          | <a href="#">1</a>         |
| kVA             | <a href="#">100</a>       |
| Connection      | <a href="#">1PhA-NT-1</a> |
| Primary Voltage | <a href="#">480</a>       |



|                            |  |
|----------------------------|--|
| Primary Max Current        | <a href="#">208.3A</a>   |
| Primary Markings           | <a href="#">H0-H1</a>  |
| Primary Terminals          | <a href="#">600MCM-2</a>   |
| Secondary Voltage          | <a href="#">240</a>  |
| Secondary Max Current      | <a href="#">416.7A</a>   |
| Secondary Markings         | <a href="#">X0-X1</a>  |
| Secondary Terminals        | <a href="#">Pads</a>   |
| Primary Taps               | <a href="#">N/A</a>  |
| Conductor Material         | <a href="#">Copper</a>   |
| Insuation Class            | <a href="#">220°C</a>  |
| BIL (Insulation) Level     | <a href="#">10kV</a>   |
| Efficiency                 | <a href="#">N/A</a>  |
| Impedance                  | <a href="#">2.5 – 4.5%</a>   |
| Sound (db)                 | <a href="#">50</a>   |
| Enclosure Type             | <a href="#">NEMA 3R Indoor</a>   |
| Enclosure                  | <a href="#">E3R-6</a>  |
| Finish                     | <a href="#">Polyster Powder Coat – ANSI/ASA 61 Grey</a>  |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |