


OFFICIAL QUOTE MP3A15H-M/BO/CLC






MP3A15H-M/BO/CLC


\$8,839.11 USD

SKU: 136db219965d

Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES







OFFICIAL QUOTE MP3A15H-M/BO/CLC



PRODUCT SPECIFICATIONS

Weight	475 lbs
Phases	<u>3</u>
Circuit Breaker Suitability	Eaton Type BAB
kVA	<u>15</u>
Connection	MPC3P-5t
Incoming Voltage	480
Primary Breaker	<u>40A</u>
Interruping Rating	14kAIC @ 480V
Output Voltage	<u>208Y/120</u>
Secondary Breaker	<u>50A</u>
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
Insuation Class	200°C
Panel Board	Bolt-On
Load Center Bus Material	Copper
# of Circuits	30
Impedance	1.5 - 3.0%
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-2B
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, ISO 9001:2015 Registered