



OFFICIAL QUOTE

25KVA 200 VOLTS TO 380 VOLTS SINGLE PHASE AUTOTRANSFORMER



25KVA 200 VOLTS TO 380 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$2,277.00 CAD

Single Phase Autotransformer with a capacity of 25kVA, transforming 200 Volts to 380 Volts

SKU: MC25B1-F

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 25kVA, transforming 200 Volts to 380 Volts



OFFICIAL QUOTE

25KVA 200 VOLTS TO 380 VOLTS SINGLE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	134.7 lbs
Phases	1
kVA	25
Connection	1PhA-NT-1
Primary Voltage	200
Primary Max Current	72.2A
Primary Markings	X0-X1
Primary Terminals	#2-14 AWG
Secondary Voltage	380
Secondary Max Current	38A
Secondary Markings	H0-H1
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-4
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

25KVA 200 VOLTS TO 380 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)