


## MC37H-C

**\$1,802.88 USD**

SKU: b917bb7c19e5

Categories: [Autotransformer](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



### PRODUCT SPECIFICATIONS

|                     |                           |
|---------------------|---------------------------|
| Weight              | 165 lbs                   |
| Phases              | <a href="#">1</a>         |
| kVA                 | <a href="#">37.5</a>      |
| Connection          | <a href="#">1PhA-NT-1</a> |
| Primary Voltage     | <a href="#">480</a>       |
| Primary Max Current | <a href="#">78.1A</a>     |
| Primary Markings    | <a href="#">H0-H1</a>     |



|                                       |  |
|---------------------------------------|--|
| <b>Primary Terminals</b>              | <a href="#">#2-14 AWG</a>  |
| <b>Secondary Voltage</b>              | <a href="#">240</a>  |
| <b>Secondary Max Current</b>          | <a href="#">156.3A</a>   |
| <b>Secondary Markings</b>             | <a href="#">X0-X1</a>  |
| <b>Secondary Terminals</b>            | <a href="#">300MCM-6</a>   |
| <b>Primary Taps</b>                   | <a href="#">N/A</a>  |
| <b>Conductor Material</b>             | <a href="#">Copper</a>   |
| <b>Insulation Class</b>               | <a href="#">220°C</a>  |
| <b>BIL (Insulation) Level</b>         | <a href="#">10kV</a>   |
| <b>Efficiency</b>                     | <a href="#">N/A</a>  |
| <b>Impedance</b>                      | <a href="#">2.5 – 4.5%</a>   |
| <b>Sound (db)</b>                     | <a href="#">50</a>   |
| <b>Enclosure Type</b>                 | <a href="#">NEMA 3R Indoor</a>   |
| <b>Enclosure</b>                      | <a href="#">E3R-4</a>  |
| <b>Finish</b>                         | <a href="#">Polyster Powder Coat – ANSI/ASA 61 Grey</a>  |
| <b>Standards &amp; Certifications</b> | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |