



37.5KVA 200 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$3,322.10 CAD

Single Phase Autotransformer with a capacity of 37.5kVA, transforming 200 Volts to 480 Volts

SKU: MC37B1-H

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 37.5kVA, transforming 200 Volts to 480 Volts



PRODUCT SPECIFICATIONS

Weight	208.1 lbs
Phases	1
kVA	37.5
Connection	1PhA-NT-1
Primary Voltage	200
Primary Max Current	108.3A
Primary Markings	X0-X1
Primary Terminals	#2/0-6 AWG
Secondary Voltage	480
Secondary Max Current	45.1A
Secondary Markings	H0-H1
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

37.5KVA 200 VOLTS TO 480 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------