


OFFICIAL QUOTE

45KVA 600 VOLTS TO 240 VOLTS THREE PHASE ENCAPSULATED AUTOTRANSFORMER





45KVA 600 VOLTS TO 240 VOLTS THREE PHASE ENCAPSULATED AUTOTRANSFORMER


\$4,347.38 USD


Three Phase Encapsulated Autotransformer with a capacity of 45kVA, transforming 600Y Volts to 240Y Volts

SKU: RC45J-C/EP

Categories: Encapsulated Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Encapsulated Autotransformer with a capacity of 45kVA, transforming 600Y Volts to 240Y Volts



OFFICIAL QUOTE



45KVA 600 VOLTS TO 240 VOLTS THREE PHASE ENCAPSULATED AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	630 lbs
Phases	3
kVA	45
Connection	3PhA-NT-1
Primary Voltage	600
Primary Markings	H1-H2-H3
Primary Terminals	#2-14 AWG
Secondary Voltage	240
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	#2/0-6 AWG
Primary Taps	N/A
Conductor Material	Copper
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>0.5 – 1.5%</u>
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-3PEP-5</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	130°C
Insuation Class	200°C (Class N)