

OFFICIAL QUOTE

CE350K-L





CE350K-L

\$217.26 USD

SKU: a2999793d5b6

Categories: Control Transformers

PRODUCT SPECIFICATIONS

Weight	5 lbs
Phases	1
VA	350
Connection	1Ph-CT-DD-SU
Primary Voltage	120/240
Primary Max Current	2.92A



OFFICIAL QUOTE

CE350K-L



Primary Markings	<u>X1-X2-X3-X4</u>
Primary Terminals	<u>Leads</u>
Secondary Voltage	240/480
Secondary Max Current	<u>1.46A</u>
Secondary Markings	<u>H1-H2-H3-H4</u>
Secondary Terminals	<u>Leads</u>
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Temperatue Rise	80°C
Insuation Class	<u>130°C</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency	N/A
Impedance	<u>5.0 – 7.0%</u>
Sound (db)	40
Enclosure Type	Type-1 Indoor
Enclosure	See Chart
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered
Finish	Semigloss - BlackSemigloss - Black