


MP39J-M/BO/CLC


\$9,302.35 USD

SKU: 0f710a9e3102

Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES







OFFICIAL QUOTE MP39J-M/BO/CLC



PRODUCT SPECIFICATIONS

Weight	315 lbs
Phases	<u>3</u>
Circuit Breaker Suitability	Eaton Type BAB
kVA	9
Connection	MPC3P-3t
Incoming Voltage	600
Primary Breaker	<u>20A</u>
Interruping Rating	14kAIC @ 600V
Output Voltage	<u>208Y/120</u>
Secondary Breaker	<u>30A</u>
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	<u>+/- 1 x 5%</u>
Conductor Material	<u>Copper</u>
Insuation Class	200°C
Panel Board	Bolt-On
Load Center Bus Material	Copper
# of Circuits	<u>18</u>
Impedance	1.5 - 3.0%
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-1B
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, ISO 9001:2015 Registered