


OFFICIAL QUOTE

5KVA 347 VOLTS TO 208 VOLTS SINGLE PHASE AUTOTRANSFORMER





5KVA 347 VOLTS TO 208 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$894.20 CAD

Single Phase Autotransformer with a capacity of 5kVA, transforming 347 Volts to 208 Volts

SKU: MC5E-B

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 5kVA, transforming 347 Volts to 208 Volts



OFFICIAL QUOTE



5KVA 347 VOLTS TO 208 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	61.5 lbs
Phases	1
kVA	<u>5</u>
Connection	1PhA-NT-1
Primary Voltage	347
Primary Max Current	<u>8.3A</u>
Primary Markings	<u>H0-H1</u>
Primary Terminals	Terminal Blocks
Secondary Voltage	208
Secondary Max Current	13.9A
Secondary Markings	<u>X0-X1</u>
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	<u>E1-0</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

5KVA 347 VOLTS TO 208 VOLTS SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------