



200KVA 416 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$15,096.20 CAD

Single Phase Autotransformer with a capacity of 200kVA, transforming 416 Volts to 110 Volts

SKU: MC200G-A2

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 200kVA, transforming 416 Volts to 110 Volts



PRODUCT SPECIFICATIONS

Weight	1125.6 lbs
Phases	1
kVA	200
Connection	1PhA-NT-1
Primary Voltage	416
Primary Max Current	277.6A
Primary Markings	H0-H1
Primary Terminals	Pads
Secondary Voltage	110
Secondary Max Current	1049.7A
Secondary Markings	X0-X1
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	55 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8S
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

200KVA 416 VOLTS TO 110 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------