



SC7J-K \$1,119.43 USD

SKU: 64459d694c7d Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

| Weight | 120 lbs |
|---------------------|--------------------|
| Phases | 1 |
| kVA | 7.5 |
| Connection | 1Ph-1coil-3T-SD |
| Primary Voltage | <u>600</u> |
| Primary Max Current | <u>12.5A</u> |
| Primary Markings | <u>H1-H2-H3-H4</u> |

The quote is valid 30 days from 19 April 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



SC7J-K



| Primary Terminals | <u>#2-14 AWG</u> |
|----------------------------|---|
| Secondary Voltage | 120/240 |
| Secondary Max Current | <u>62.5A</u> |
| Secondary Markings | <u>X1-X3-X2-X4</u> |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | <u>+/-1 x 5%</u> |
| Conductor Material | Copper |
| Insuation Class | <u>220°C</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Impedance | <u>5.5 – 7.0%</u> |
| Sound (db) | <u>40</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | <u>E3R-4</u> |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Efficiency | N/A |
| | |