



**RS15G**

**\$639.99 USD**

SKU: ffb63b77f901

Categories: [Motor Starters](#)

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



#### PRODUCT SPECIFICATIONS

Weight	45 lbs
Phases	<a href="#">3</a>
HP	<a href="#">15</a>
Connection	<a href="#">3PhA-ST-0-2</a>
Primary Voltage	<a href="#">416</a>
Primary Max Current	<a href="#">20.8A</a>



Primary Markings	<a href="#">H1-H2-H3</a>
Primary Terminals	<a href="#">Large Screws</a>
Secondary Voltage	<a href="#">65/80/100%</a>
Secondary Max Current	<a href="#">133.2A</a>
Secondary Markings	<a href="#">A-B-C</a>
Secondary Terminals	<a href="#">Large Screws</a>
Primary Taps	<a href="#">N/A</a>
Conductor Material	<a href="#">Copper</a>
Temperatue Rise	<a href="#">115°C</a>
Insuation Class	<a href="#">180°C</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency	<a href="#">N/A</a>
Impedance	<a href="#">N/A</a>
Sound (db)	<a href="#">N/A</a>
Enclosure Type	<a href="#">Core &amp; Coil</a>
Enclosure	<a href="#">N/A</a>
Finish	<a href="#">N/A</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>