



45KVA 277 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER

\$2,058.90 CAD

Three Phase Autotransformer with a capacity of 45kVA, transforming 277Y Volts to 347Y Volts

SKU: RC45D-E

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 45kVA, transforming 277Y Volts to 347Y Volts



PRODUCT SPECIFICATIONS

Weight	68 lbs
Phases	3
kVA	45
Connection	3PhA-NT-1
Primary Voltage	120/240
Primary Max Current	93.8A
Primary Markings	X1-X2-X3
Primary Terminals	#2/0-6 AWG
Secondary Voltage	347
Secondary Max Current	74.9A
Secondary Markings	H1-H2-H3
Secondary Terminals	#2/0-6 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	45
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

45KVA 277 VOLTS TO 347 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------