

**OFFICIAL QUOTE** 

# 75KVA 208 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER





# 75KVA 208 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER

# \$3,208.95 USD

Three Phase Autotransformer with a capacity of 75kVA, transforming 208Y Volts to 347Y Volts

SKU: RC75B-E Categories: <u>Autotransformer</u>

# SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 75kVA, transforming 208Y Volts to 347Y Volts



**OFFICIAL QUOTE** 

## 75KVA 208 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER



### **PRODUCT SPECIFICATIONS**

Weight	224 lbs
Phases	<u>3</u>
kVA	<u>75</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	208
Primary Max Current	<u>208.2A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	600MCM-2
Secondary Voltage	<u>347</u>
Secondary Max Current	<u>124.8A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	<u>300MCM-6</u>
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insulation Class	<u>220°C (Class H)</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	<u>N/A</u>
Impedance Range	<u>1.5 – 3.5%</u>
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-6</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



**OFFICIAL QUOTE** 

## 75KVA 208 VOLTS TO 347 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM