


OFFICIAL QUOTE

75KVA 415 VOLTS TO 200 VOLTS THREE PHASE AUTOTRANSFORMER





75KVA 415 VOLTS TO 200 VOLTS THREE PHASE AUTOTRANSFORMER


\$3,486.04 USD

Three Phase Autotransformer with a capacity of 75kVA, transforming 415Y Volts to 200Y Volts

SKU: RA75G2-B1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 75kVA, transforming 415Y Volts to 200Y Volts



OFFICIAL QUOTE



75KVA 415 VOLTS TO 200 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	226 lbs
Phases	<u>3</u>
kVA	<u>75</u>
Connection	3PhA-NT-1
Primary Voltage	415
Primary Max Current	<u>104.3A</u>
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	#2/0-6 AWG
Secondary Voltage	200
Secondary Max Current	216.5A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	<u>45</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-6</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

75KVA 415 VOLTS TO 200 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------