

OFFICIAL QUOTE

750KVA 416 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER





750KVA 416 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER

\$8,360.78 USD

Three Phase Autotransformer with a capacity of 750kVA, transforming 416Y Volts to 480Y Volts

SKU: RA750G-H Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 750kVA, transforming 416Y Volts to 480Y Volts



OFFICIAL QUOTE

750KVA 416 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	671 lbs
Phases	<u>3</u>
kVA	750
Connection	<u>3PhA-NT-1</u>
Primary Voltage	<u>416</u>
Primary Max Current	<u>1040.9A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	Pads
Secondary Voltage	<u>480</u>
Secondary Max Current	<u>902.1A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	<u>220°C (Class H)</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	<u>N/A</u>
Impedance Range	<u>0.5 – 1.5%</u>
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

750KVA 416 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM