

OFFICIAL QUOTE

75KVA 400 VOLTS TO 200 VOLTS SINGLE PHASE AUTOTRANSFORMER





75KVA 400 VOLTS TO 200 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$5,045.90 CAD

Single Phase Autotransformer with a capacity of 75kVA, transforming 400 Volts to 200 Volts

SKU: MC75G1-B1 Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 75kVA, transforming 400 Volts to 200 Volts



OFFICIAL QUOTE

75KVA 400 VOLTS TO 200 VOLTS SINGLE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| Weight | 325.1 lbs |
|----------------------------|---|
| Phases | 1 |
| kVA | <u>75</u> |
| Connection | <u>1PhA-NT-1</u> |
| Primary Voltage | <u>400</u> |
| Primary Max Current | <u>108.3A</u> |
| Primary Markings | <u>H0-H1</u> |
| Primary Terminals | <u>#2/0-6 AWG</u> |
| Secondary Voltage | 200 |
| Secondary Max Current | <u>216.5A</u> |
| Secondary Markings | <u>X0-X1</u> |
| Secondary Terminals | 600MCM-2 |
| Primary Taps | N/A |
| Conductor Material | <u>Copper</u> |
| Insulation Class | <u>220°C (Class H)</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | <u>N/A</u> |
| Impedance Range | <u>1.5 – 3.5%</u> |
| Sound (db) | <u>45 dB</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-6</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

75KVA 400 VOLTS TO 200 VOLTS SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM