



75KVA 400 VOLTS TO 200 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$5,045.90 CAD

Single Phase Autotransformer with a capacity of 75kVA, transforming 400 Volts to 200 Volts

SKU: MC75G1-B1

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 75kVA, transforming 400 Volts to 200 Volts



PRODUCT SPECIFICATIONS

Weight	325.1 lbs
Phases	1
kVA	75
Connection	1PhA-NT-1
Primary Voltage	400
Primary Max Current	108.3A
Primary Markings	H0-H1
Primary Terminals	#2/0-6 AWG
Secondary Voltage	200
Secondary Max Current	216.5A
Secondary Markings	X0-X1
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

75KVA 400 VOLTS TO 200 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------