

#### **OFFICIAL QUOTE**

## 112.5KVA 575 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER





# 112.5KVA 575 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$11,412.88 USD

Three Phase Isolation Transformer with a capacity of 112.5kVA, transforming 575 Volts to 220Y/127 Volts

SKU: BC112J1-S2/Z3

**Categories:** <u>Isolation Transformers</u>

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 112.5kVA, transforming 575 Volts to 220Y/127 Volts



## **OFFICIAL QUOTE**



# 112.5KVA 575 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

#### PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS     |  |  |
|----------------------------|--|--|
| Weight                     | 890 lbs  |  |
| Phases                     | <u>3</u>   |  |
| kVA                        | 112.5  |  |
| Connection                 | 3Ph-DY-5T-SD   |  |
| Primary Voltage            | <u>575</u>   |  |
| Primary Max Current        | 112.96A  |  |
| Primary Markings           | H1-H2-H3   |  |
| Primary Terminals          | 300 MCM - 6  |  |
| Secondary Voltage          | 220Y/127   |  |
| Secondary Max Current      | 295.24A  |  |
| Secondary Markings         | <u>X0-X1-X2-X3</u>   |  |
| Secondary Terminals        | 300 MCM - 6  |  |
| Primary Taps               | +/- 2 x 2.5%   |  |
| Conductor Material         | Copper   |  |
| BIL (Insulation) Level     | <u>10kV</u>  |  |
| Efficiency (@35% Load) %   | 98.74% (DOE 2016/NRCan 2019)   |  |
| Impedance Range            | 4.0 - 6.0%   |  |
| Sound (db)                 | 50   |  |
| Enclosure Type             | NEMA 3R Indoor   |  |
| Enclosure Size             | E3R-8  |  |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey   |  |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |  |
| Temperatue Rise            | 150°C  |  |



## **OFFICIAL QUOTE**



# 112.5KVA 575 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

| Insuation Class      | 150°C                                    | _ |
|----------------------|--|---|
| Country/Manufacturer | Canada/RPM                               |   |
| Finish/Colour        | Polyester Powder Coat – ANSI/ASA 61 Grey |   |