

OFFICIAL QUOTE

112.5KVA 550 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER





112.5KVA 550 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$11,888.42 USD


Three Phase Isolation Transformer with a capacity of 112.5kVA, transforming 550 Volts to 220Y/127 Volts

SKU: BC112J2-S2/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Isolation Transformer with a capacity of 112.5kVA, transforming 550 Volts to 220Y/127 Volts



OFFICIAL QUOTE



112.5KVA 550 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | | |
|----------------------------|--------------------------------------------------------------------------------------|--|
| Weight | 890 lbs | |
| Phases | <u>3</u> | |
| kVA | 112.5 | |
| Connection | 3Ph-DY-5T-SD | |
| Primary Voltage | <u>550</u> | |
| Primary Max Current | 118.09A | |
| Primary Markings | H1-H2-H3 | |
| Primary Terminals | <u>300 MCM - 6</u> | |
| Secondary Voltage | 220Y/127 | |
| Secondary Max Current | 295.24A | |
| Secondary Markings | <u>X0-X1-X2-X3</u> | |
| Secondary Terminals | <u>300 MCM - 6</u> | |
| Primary Taps | +/- 2 x 2.5% | |
| Conductor Material | Copper | |
| BIL (Insulation) Level | <u>10kV</u> | |
| Efficiency (@35% Load) % | 98.74% (DOE 2016/NRCan 2019) | |
| Impedance Range | 4.0 - 6.0% | |
| Sound (db) | <u>50</u> | |
| Enclosure Type | NEMA 3R Indoor | |
| Enclosure Size | E3R-8 | |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey | |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered | |
| Temperatue Rise | 150°C | |



OFFICIAL QUOTE



112.5KVA 550 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

| Insuation Class | 150°C |
|----------------------|------------------------------------------|
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |