

#### **OFFICIAL QUOTE**

## 225KVA 110 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER





## 225KVA 110 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER


\$15,546.30 CAD

Three Phase Autotransformer with a capacity of 225kVA, transforming 110Y Volts to 415Y Volts

**SKU:** RA225A2-G2

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 225kVA, transforming 110Y Volts to 415Y Volts



### **OFFICIAL QUOTE**

## 225KVA 110 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER



### **PRODUCT SPECIFICATIONS**

| Weight                     | 1089 lbs   |
|----------------------------|--|
| Phases                     | <u>3</u>   |
| kVA                        | 225  |
| Connection                 | 3PhA-NT-1  |
| Primary Voltage            | 110  |
| Primary Max Current        | 1180.9A  |
| Primary Markings           | <u>X1-X2-X3</u>  |
| Primary Terminals          | <u>Pads</u>  |
| Secondary Voltage          | 415  |
| Secondary Max Current      | 313A   |
| Secondary Markings         | <u>H1-H2-H3</u>  |
| Secondary Terminals        | <u>Pads</u>  |
| Primary Taps               | N/A  |
| Conductor Material         | Aluminum   |
| Insulation Class           | 220°C (Class H)  |
| BIL (Insulation) Level     | <u>10kV</u>  |
| Efficiency (@35% Load) %   | N/A  |
| Impedance Range            | 2.5 - 4.5%   |
| Sound (db)                 | 60   |
| Enclosure Type             | NEMA 3R Indoor   |
| Enclosure Size             | <u>E3R-8</u>   |
| Finish/Colour              | Polyester Powder Coat – ANSI/ASA 61 Grey   |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



### **OFFICIAL QUOTE**

# 225KVA 110 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|