



## 45VA 200 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

**\$5,494.94 CAD**

Three Phase Isolation Transformer with a capacity of 45kVA, transforming 200 Volts to 415Y/240 Volts

SKU: BA45B1-N2/Z3

Categories: [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 45kVA, transforming 200 Volts to 415Y/240 Volts



## PRODUCT SPECIFICATIONS

Weight	390 lbs
Phases	<a href="#">3</a>
kVA	<a href="#">45</a>
Connection	<a href="#">3Ph-DY-5T-SU</a>
Primary Voltage	<a href="#">200</a>
Primary Max Current	<a href="#">129.9A</a>
Primary Markings	<a href="#">X1-X2-X3</a>
Primary Terminals	<a href="#">300 MCM – 6</a>
Secondary Voltage	<a href="#">415Y/240</a>
Secondary Max Current	<a href="#">62.6A</a>
Secondary Markings	<a href="#">H0-H1-H2-H3</a>
Secondary Terminals	<a href="#">300 MCM – 6</a>
Primary Taps	<a href="#">+/- 2 x 2.5%</a>
Conductor Material	<a href="#">Aluminum</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">98.40% (DOE 2016/NRCAN 2019)</a>
Impedance Range	<a href="#">4.0 – 6.0%</a>
Sound (db)	<a href="#">45</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-6</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Temperature Rise	<a href="#">150°C</a>



OFFICIAL QUOTE

45VA 200 VOLTS TO 415Y/240 VOLTS  
THREE PHASE ISOLATION  
TRANSFORMER



Insuation Class	<a href="#">150°C</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>