



100KVA 440 VOLTS TO 550 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$3,300.00 CAD

Single Phase Autotransformer with a capacity of 100kVA, transforming 440 Volts to 550 Volts

SKU: MC100H2-J2

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 100kVA, transforming 440 Volts to 550 Volts



PRODUCT SPECIFICATIONS

Weight	204.1 lbs
Phases	1
kVA	100
Connection	1PhA-NT-1
Primary Voltage	440
Primary Max Current	131.2A
Primary Markings	X0-X1
Primary Terminals	300MCM-6
Secondary Voltage	550
Secondary Max Current	105A
Secondary Markings	H0-H1
Secondary Terminals	#2/0-6 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-4
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

100KVA 440 VOLTS TO 550 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------