

OFFICIAL QUOTE

330KVA 220 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





330KVA 220 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$26,130.94 CAD


Single Phase Isolation Transformer with a capacity of 330kVA, transforming 220 Volts to 220/440 Volts

SKU: SC330C2-L2/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 330kVA, transforming 220 Volts to 220/440 Volts



OFFICIAL QUOTE



330KVA 220 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | | |
|----------------------------|--|--|
| Weight | 1720 lbs | |
| Phases | 1 | |
| kVA | 330 | |
| Connection | 1Ph-2coil-5T-SU | |
| Primary Voltage | 220 | |
| Primary Max Current | 1500.0A | |
| Primary Markings | H1-H2 | |
| Primary Terminals | <u>Pads</u> | |
| Secondary Voltage | 220/440 | |
| Secondary Max Current | 1500.0A | |
| Secondary Markings | <u>X1-X2</u> | |
| Secondary Terminals | <u>Pads</u> | |
| Primary Taps | +/- 2 x 2.5% | |
| Conductor Material | Copper | |
| BIL (Insulation) Level | 10kV | |
| Efficiency (@35% Load) % | 98.90% (DOE 2016/NRCan 2019) | |
| Impedance Range | 4.0 - 6.0% | |
| Sound (db) | <u>55</u> | |
| Enclosure Type | NEMA 3R Indoor | |
| Enclosure Size | E3R-9S | |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey | |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered | |
| Temperatue Rise | 150°C | |



OFFICIAL QUOTE



330KVA 220 VOLTS TO 220/440 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

| Insuation Class | 150°C |
|----------------------|--|
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |