



**75KVA 277 VOLTS TO 415Y/240
VOLTS THREE PHASE ISOLATION
TRANSFORMER**



**75KVA 277 VOLTS TO
415Y/240 VOLTS THREE
PHASE ISOLATION
TRANSFORMER**

\$7,918.97 CAD

Three Phase Isolation Transformer with a capacity of 75kVA, transforming 277 Volts to 415Y/240 Volts

SKU: BA75D-N2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 75kVA, transforming 277 Volts to 415Y/240 Volts



PRODUCT SPECIFICATIONS

Weight	607 lbs
Phases	3
kVA	75
Connection	3Ph-DY-5T-SU
Primary Voltage	277
Primary Max Current	156.32A
Primary Markings	X1-X2-X3
Primary Terminals	300 MCM – 6
Secondary Voltage	415Y/240
Secondary Max Current	104.34A
Secondary Markings	H0-H1-H2-H3
Secondary Terminals	300 MCM – 6
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.50% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	50
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C

OFFICIAL QUOTE

75KVA 277 VOLTS TO 415Y/240
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey