

#### **OFFICIAL QUOTE**

### 300VA 110 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER





## 300VA 110 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER


\$26,836.99 CAD

Three Phase Isolation Transformer with a capacity of 300kVA, transforming 110 Volts to 415Y/240 Volts

**SKU:** BA300A2-N2/Z3

**Categories:** <u>Isolation Transformers</u>

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



$$X_2$$
 $X_2$ 
 $X_3$ 
 $X_4$ 
 $X_5$ 
 $X_6$ 
 $X_7$ 
 $X_8$ 
 $X_8$ 

Three Phase Isolation Transformer with a capacity of 300kVA, transforming 110 Volts to 415Y/240 Volts



#### **OFFICIAL QUOTE**



# 300VA 110 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

### **PRODUCT SPECIFICATIONS**

| Weight                     | 2100 lbs                                                                             |
|----------------------------|--------------------------------------------------------------------------------------|
| Phases                     | 3                                                                                    |
| kVA                        | 300                                                                                  |
| Connection                 | 3Ph-DY-5CT-SU                                                                        |
| Primary Voltage            | 110                                                                                  |
| Primary Max Current        | <u>1574.59A</u>                                                                      |
| Primary Markings           | <u>X1-X2-X3</u>                                                                      |
| Primary Terminals          | <u>Pads</u>                                                                          |
| Secondary Voltage          | 415Y/240                                                                             |
| Secondary Max Current      | 417.36A                                                                              |
| Secondary Markings         | <u>H0-H1-H2-H3</u>                                                                   |
| Secondary Terminals        | <u>Pads</u>                                                                          |
| Primary Taps               | +/- 2 x 2.5%                                                                         |
| Conductor Material         | Aluminum                                                                             |
| BIL (Insulation) Level     | <u>10kV</u>                                                                          |
| Efficiency (@35% Load) %   | 99.02% (DOE 2016/NRCan 2019)                                                         |
| Impedance Range            | 4.0 - 6.0%                                                                           |
| Sound (db)                 | <u>55</u>                                                                            |
| Enclosure Type             | NEMA 3R Indoor                                                                       |
| Enclosure Size             | E3R-9                                                                                |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey                                             |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise            | 150°C                                                                                |



#### **OFFICIAL QUOTE**



# 300VA 110 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

| Insuation Class      | <u>150°C</u>                             |
|----------------------|------------------------------------------|
| Country/Manufacturer | Canada/RPM                               |
| Finish/Colour        | Polyester Powder Coat – ANSI/ASA 61 Grey |