

#### **OFFICIAL QUOTE**

### 75KVA 240 VOLTS TO 120 VOLTS THREE PHASE AUTOTRANSFORMER





### 75KVA 240 VOLTS TO 120 VOLTS THREE PHASE AUTOTRANSFORMER


\$3,399.17 USD

Three Phase Autotransformer with a capacity of 75kVA, transforming 240Y Volts to 120Y Volts

SKU: RA75C-A

**Categories:** Autotransformer

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Three Phase Autotransformer with a capacity of 75kVA, transforming 240Y Volts to 120Y Volts



#### **OFFICIAL QUOTE**



## 75KVA 240 VOLTS TO 120 VOLTS THREE PHASE AUTOTRANSFORMER

#### PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS     |   |
|----------------------------|---|
| Weight                     | 217 lbs   |
| Phases                     | <u>3</u>  |
| kVA                        | <u>75</u>   |
| Connection                 | 3PhA-NT-1   |
| Primary Voltage            | 240   |
| Primary Max Current        | 180.4A  |
| Primary Markings           | H1-H2-H3  |
| Primary Terminals          | 300MCM-6  |
| Secondary Voltage          | 120   |
| Secondary Max Current      | 360.8A  |
| Secondary Markings         | <u>X1-X2-X3</u>   |
| Secondary Terminals        | <u>Pads</u>   |
| Primary Taps               | N/A   |
| Conductor Material         | Aluminum  |
| Insulation Class           | 220°C (Class H)   |
| BIL (Insulation) Level     | 10kV  |
| Efficiency (@35% Load) %   | N/A   |
| Impedance Range            | 1.5 - 3.5%  |
| Sound (db)                 | 45  |
| Enclosure Type             | NEMA 3R Indoor  |
| Enclosure Size             | E3R-6   |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey  |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015  Registered |



#### **OFFICIAL QUOTE**

# 75KVA 240 VOLTS TO 120 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | <u>Canada/RPM</u> |
|----------------------|-------------------|
|----------------------|-------------------|