


OFFICIAL QUOTE

50KVA 277 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





50KVA 277 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$4,086.36 USD


Single Phase Isolation Transformer with a capacity of 50kVA, transforming 277 Volts to 415 Volts

SKU: SC50D-G2/Z3

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 50kVA, transforming 277 Volts to 415 Volts



OFFICIAL QUOTE



50KVA 277 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS		
Weight	348 lbs	
Phases	1	
kVA	<u>50</u>	
Connection	1Ph-2coil-5T-SU	
Primary Voltage	277	
Primary Max Current	180.51A	
Primary Markings	<u>X1-X2</u>	
Primary Terminals	<u>300 MCM - 6</u>	
Secondary Voltage	415	
Secondary Max Current	<u>120.48A</u>	
Secondary Markings	H1-H2	
Secondary Terminals	<u>300 MCM - 6</u>	
Primary Taps	+/- 2 x 2.5%	
Conductor Material	Copper	
BIL (Insulation) Level	<u>10kV</u>	
Efficiency (@35% Load) %	98.30% (DOE 2016/NRCan 2019)	
Impedance Range	4.0 - 6.0%	
Sound (db)	45	
Enclosure Type	NEMA 3R Indoor	
Enclosure Size	<u>E3R-6</u>	
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey	
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered	
Temperatue Rise	150°C	



OFFICIAL QUOTE



50KVA 277 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey