



OFFICIAL QUOTE

150KVA 460 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER



150KVA 460 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER

\$3,801.30 CAD

Three Phase Autotransformer with a capacity of 150kVA, transforming 460Y Volts to 550Y Volts

SKU: RC150H1-J2

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 150kVA, transforming 460Y Volts to 550Y Volts



OFFICIAL QUOTE

150KVA 460 VOLTS TO 550 VOLTS
THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	214 lbs
Phases	3
kVA	150
Connection	3PhA-NT-1
Primary Voltage	460
Primary Max Current	188.3A
Primary Markings	X1-X2-X3
Primary Terminals	600MCM-2
Secondary Voltage	550
Secondary Max Current	157.5A
Secondary Markings	H1-H2-H3
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

**150KVA 460 VOLTS TO 550 VOLTS
THREE PHASE AUTOTRANSFORMER**



Country/Manufacturer	Canada/RPM
-----------------------------	----------------------------