



OFFICIAL QUOTE

350VA 120/240 VOLTS TO 12/24 VOLTS SINGLE PHASE CONTROL TRANSFORMER



350VA 120/240 VOLTS TO 12/24 VOLTS SINGLE PHASE CONTROL TRANSFORMER

\$251.16 CAD



Single Phase Control Transformer with a capacity of 350VA, transforming 120/240 Volts to 12/24 Volts

SKU: CS350K-Z

Categories: [Control Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES

VA Rating	Overall Dimensions (inches)				Mounting Slot
	A	B	C	F	
25	1	3	2.5	2.5	3.33 0.25x0.625
50	1	3	2.5	2.5	3.33 0.25x0.625
100	1	4	2.5	2.5	3.75 0.25x0.625
150	3.75	4.25	3.33	3.25	3.5 0.25x0.625
200	3.75	4.5	3.33	3.25	3.5 0.25x0.625
250	3.75	5	3.33	3.25	3.5 0.31x0.625
350	4.5	5	3.75	3.75	4.75 0.31x0.625
500	5.25	5	4.38	4.5	5.75 0.31x0.625
750	5.25	5.5	4.38	4.5	5.75 0.31x0.625
1000	5.25	6.5	4.38	4.5	5.75 0.31x0.625
1500	6.75	7.25	5.63	5	5.75 0.31x0.625
2000	7.5	7.5	6.25	6	4.25 0.31x0.625
3000	7.5	8.75	6.25	6	5.5 0.31x0.625
5000	9	10	8	7	8 0.44x0.625



Single Phase Control Transformer with a capacity of 350VA, transforming 120/240 Volts to 12/24 Volts



OFFICIAL QUOTE

350VA 120/240 VOLTS TO 12/24
VOLTS SINGLE PHASE CONTROL
TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	40 lbs
Phases	1
Connection	1Ph-CT-DD-SD
Primary Voltage	120/240
Primary Max Current	2.92A
Primary Markings	H1-H2-H3-H4
Primary Terminals	Terminals
Secondary Voltage	12/24
Secondary Max Current	29.17A
Secondary Markings	X1-X2-X3-X4
Secondary Terminals	Terminals
Primary Taps	N/A
Conductor Material	Copper
Temperature Rise	80°C
Insulation Class	130°C (Class B)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	5.0 – 7.0%
Sound (db)	40
Enclosure Type	Core & Coil
Enclosure Size	See Core & Coil Chart
Finish/Colour	N/A
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered



OFFICIAL QUOTE



350VA 120/240 VOLTS TO 12/24
VOLTS SINGLE PHASE CONTROL
TRANSFORMER

VA	350
Country/Manufacturer	Canada/RPM