

OFFICIAL QUOTE

1500KVA 416 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER





1500KVA 416 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER


\$31,793.00 CAD


Three Phase Autotransformer with a capacity of 1500kVA, transforming 416Y Volts to 600Y Volts

SKU: RA1500G-J

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 1500kVA, transforming 416Y Volts to 600Y Volts



OFFICIAL QUOTE



1500KVA 416 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	2981 lbs
Phases	<u>3</u>
kVA	<u>1500</u>
Connection	3PhA-NT-1
Primary Voltage	416
Primary Max Current	2081.8A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	600
Secondary Max Current	<u>1443.4A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 - 3.0%
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-10
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

1500KVA 416 VOLTS TO 600 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------